

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name : Instru Suc
UFI : AWD0-309X-C006-2H8H

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Use of the substance/mixture : instruments disinfection
Medical device
(IIb)

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Supplier**

Laboratorium Dr. Deppe GmbH
Hooghe Weg 35
D-47906 Kempen
T +49 21 52 55 65 0 - F +49 21 52 50 84 9
sdb@dr-deppe.de - www.dr-deppe.de

Email competent person

sdb@dr-deppe.de

1.4. Emergency telephone number

Emergency number : INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects

Causes serious eye damage. Causes severe skin burns and eye damage. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Flammable liquid and vapour.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS05

GHS09

Signal word (CLP) :

Danger

Contains :

dimethyldioctylammonium chloride

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.

H314 - Causes severe skin burns and eye damage.

H410 - Very toxic to aquatic life with long lasting effects.

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 - Do not breathe gas, mist, vapours, spray.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P310 - Immediately call a POISON CENTER, a doctor.

2.3. Other hazards

PBT: not relevant – no registration required
vPvB: not relevant – no registration required

Component	
dimethyldioctylammonium chloride (5538-94-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propan-2-ol (67-63-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-(2-butoxyethoxy)ethanol (112-34-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethanol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyldioctylammonium chloride	(CAS-No.) 5538-94-3 (EC-No.) 226-901-0 (REACH-no) 01-2120767055-53-xxxx	≥ 5 – < 10	Acute Tox. 3 (Oral), H301 (ATE=238 mg/kg bodyweight) Acute Tox. 2 (Dermal), H310 (ATE=170.3 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410
propan-2-ol substance with national workplace exposure limit(s) (GB)	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0 (REACH-no) 01-2119457558-25-xxxx	≥ 5 – < 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-(2-butoxyethoxy)ethanol substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	(CAS-No.) 112-34-5 (EC-No.) 203-961-6 (EC Index-No.) 603-096-00-8 (REACH-no) 01-2119475104-44-xxxx	≥ 5 – < 10	Eye Irrit. 2, H319

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

ethanol substance with national workplace exposure limit(s) (GB)	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43-xxxx	≥ 1 – < 2.5	Flam. Liq. 2, H225 Eye Irrit. 2, H319
--	--	-------------	--

Specific concentration limits:

Name	Product identifier	Specific concentration limits
ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43-xxxx	(50 ≤C < 100) Eye Irrit. 2, H319

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Explosive vapour/air mixtures may be formed.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide. Nitrogen oxides.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe gas, mist, vapours, spray. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Notify authorities if product enters sewers or public waters. Avoid sub-soil penetration. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. Notify authorities if product enters sewers or public waters.
Other information : Disposal must be done according to official regulations.

6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : In use, may form flammable vapour-air mixture.
Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe gas, mist, vapours, spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up. Protect against frost. Keep container tightly closed.
Heat and ignition sources : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from heat and direct sunlight.
Information about storage in one common storage facility : Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

No additional information available

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

propan-2-ol (67-63-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA) [1]	999 mg/m ³
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

2-(2-butoxyethoxy)ethanol (112-34-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-(2-Butoxyethoxy)ethanol
IOEL TWA	67.5 mg/m ³
IOEL TWA [ppm]	10 ppm
IOEL STEL	101.2 mg/m ³
IOEL STEL [ppm]	15 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
United Kingdom - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
WEL TWA (OEL TWA) [1]	67.5 mg/m ³
WEL TWA (OEL TWA) [2]	10 ppm
WEL STEL (OEL STEL)	101.2 mg/m ³
WEL STEL (OEL STEL) [ppm]	15 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

ethanol (64-17-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethanol
WEL TWA (OEL TWA) [1]	1920 mg/m ³
WEL TWA (OEL TWA) [2]	1000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

8.1.4. DNEL and PNEC

propan-2-ol (67-63-0)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	500 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	26 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	89 mg/m ³
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	140.9 mg/l
PNEC aqua (marine water)	140.9 mg/l
PNEC aqua (intermittent, freshwater)	140.9 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	552 mg/kg dwt
PNEC sediment (marine water)	552 mg/kg dwt
PNEC (Soil)	
PNEC soil	28 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	160 mg/kg
PNEC (STP)	
PNEC sewage treatment plant	2251 mg/l

2-(2-butoxyethoxy)ethanol (112-34-5)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	101.2 mg/m ³
Long-term - local effects, inhalation	67.5 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	6.25 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	1.1 mg/l
PNEC aqua (marine water)	0.11 mg/l
PNEC aqua (intermittent, freshwater)	11 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	4.4 mg/kg dwt
PNEC sediment (marine water)	0.44 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.32 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	56 mg/kg food

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

dimethyldioctylammonium chloride (5538-94-3)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	18.79
Long-term - systemic effects, dermal	2.67 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	18.79 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	7.36 mg/m ³
Acute - systemic effects, oral	1.6 mg/kg bodyweight
Long-term - systemic effects, oral	1.6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	7.36 mg/m ³
Long-term - systemic effects, dermal	1.6 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.001 mg/l
PNEC aqua (marine water)	0.0001 mg/l
PNEC aqua (intermittent, freshwater)	0.00066 mg/l
PNEC (STP)	
PNEC sewage treatment plant	0.5 mg/l
ethanol (64-17-5)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	343 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	950 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	87 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	114 mg/m ³
Long-term - systemic effects, dermal	206 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.96 mg/l
PNEC aqua (marine water)	0.79 mg/l
PNEC aqua (intermittent, freshwater)	2.75 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	3.6 mg/kg dwt
PNEC sediment (marine water)	2.9 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.63 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0.38 kg/kg food
PNEC (STP)	
PNEC sewage treatment plant	580 mg/l

8.1.5. Control banding

No additional information available

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Wear closed safety glasses. EN 166. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. EN ISO 13688. EN 13034

Hand protection:

Chemically resistant protective gloves. EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	-	No additional information available	EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. EN 143. Short term exposure. A-P2. Breathing apparatus with filter. Breathing equipment is only to be used in order to handle the residual risk of short term jobs if all other risk minimizing measures have been carried out e.g. retention and/or local exhaust

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Always wash hands after handling the product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: colourless.
Appearance	: clear.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: ≈ 106 K (1013 hPa)
Flammability	: Not applicable
Explosive properties	: Product is not explosive. Explosive vapour/air mixtures may be formed.

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Oxidising properties	: Non oxidizing.
Explosive limits	: Not available
Lower explosive limit (LEL)	: 2 vol %
Upper explosive limit (UEL)	: 13.5 vol %
Flash point	: > 43 °C (1013 hPa)
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
pH	: 7 – 8.5
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: ≈ 57 hPa (19,6 °C)
Vapour pressure at 50 °C	: Not available
Density	: 0.985 – 0.9951 g/ml
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

dimethyldioctylammonium chloride (5538-94-3)

LD50 oral rat	238 mg/kg bodyweight (OECD 401 method)
LD50 dermal rabbit	170.3 mg/kg bodyweight (OECD 434)

Skin corrosion/irritation : Causes severe skin burns.
pH: 7 – 8.5

Serious eye damage/irritation : Causes serious eye damage.
pH: 7 – 8.5

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Additional information : May cause sensitisation of susceptible persons

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

propan-2-ol (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

dimethyldioctylammonium chloride (5538-94-3)

LC50 - Fish [1]	0.28 mg/l (96 h; <i>Lepomis macrochirus</i> (EPA OPP 72-1))
EC50 - Crustacea [1]	0.24 mg/l (48 h; <i>Daphnia magna</i> ; ((OECD 202 method))
ErC50 algae	0.027 mg/l (72 h; <i>Pseudokirchneriella subcapitata</i> ; (OECD 201 method))

12.2. Persistence and degradability

propan-2-ol (67-63-0)

Persistence and degradability	Readily biodegradable.
Biodegradation	53 % (5 d)

2-(2-butoxyethoxy)ethanol (112-34-5)

Persistence and degradability	Readily biodegradable.
Biodegradation	≈ 85 % (28 d; (OECD-Methode 301C))

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

dimethyldioctylammonium chloride (5538-94-3)	
Persistence and degradability	Readily biodegradable.
Biodegradation	73 – 96 % (28 d;(OECD 301B method);(OECD 301D method))

ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable.
Biodegradation	84 % (20 d)

12.3. Bioaccumulative potential

propan-2-ol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (25 °C)
Bioaccumulative potential	Bioaccumulation unlikely.

2-(2-butoxyethoxy)ethanol (112-34-5)	
Partition coefficient n-octanol/water (Log Pow)	1 (20 °C; pH 7; (OECD 117 method))
Bioaccumulative potential	Bioaccumulation unlikely.

dimethyldioctylammonium chloride (5538-94-3)	
Partition coefficient n-octanol/water (Log Pow)	1.2 (21 °C; pH 6-8; (OECD 107 method))
Bioaccumulative potential	Bioaccumulation unlikely.

ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Kow)	-0.35 (20 °C)
Bioaccumulative potential	Bioaccumulation unlikely.

12.4. Mobility in soil

propan-2-ol (67-63-0)	
Ecology - soil	Expected to be highly mobile in soil.

2-(2-butoxyethoxy)ethanol (112-34-5)	
Ecology - soil	Expected to be highly mobile in soil.

ethanol (64-17-5)	
Surface tension	22.31 mN/m (20 °C)

12.5. Results of PBT and vPvB assessment

Instru Suc	
PBT: not relevant – no registration required	
vPvB: not relevant – no registration required	

Component	
dimethyldioctylammonium chloride (5538-94-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propan-2-ol (67-63-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

2-(2-butoxyethoxy)ethanol (112-34-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethanol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Disposal must be done according to official regulations. Do not dispose of with domestic waste. Do not discharge into drains or the environment. European waste catalogue.
Product/Packaging disposal recommendations	: Recycle or dispose of in compliance with current legislation.
Additional information	: Flammable vapours may accumulate in the container.
HP Code	: HP3 - "Flammable:" — flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; — flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; — flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; — flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; — water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; — other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure. HP8 - "Corrosive:" waste which on application can cause skin corrosion. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 2920	UN 2920	UN 2920	UN 2920	UN 2920
14.2. UN proper shipping name				
CORROSIVE LIQUID, FLAMMABLE, N.O.S. (dimethyldioctylammonium chloride ; propan-2-ol)	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (dimethyldioctylammonium chloride ; propan-2-ol)	Corrosive liquid, flammable, n.o.s. (dimethyldioctylammonium chloride ; propan-2-ol)	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (dimethyldioctylammonium chloride ; propan-2-ol)	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (dimethyldioctylammonium chloride ; propan-2-ol)

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Transport document description				
UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (dimethyldioctylammonium chloride ; propan-2-ol), 8 (3), II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (dimethyldioctylammonium chloride ; propan-2-ol), 8 (3), II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 2920 Corrosive liquid, flammable, n.o.s. (dimethyldioctylammonium chloride ; propan-2-ol), 8 (3), II, ENVIRONMENTALLY HAZARDOUS	UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (dimethyldioctylammonium chloride ; propan-2-ol), 8 (3), II, ENVIRONMENTALLY HAZARDOUS	UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (dimethyldioctylammonium chloride ; propan-2-ol), 8 (3), II, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
8 (3)	8 (3)	8 (3)	8 (3)	8 (3)
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : CF1
 Special provisions (ADR) : 274
 Limited quantities (ADR) : 1I
 Excepted quantities (ADR) : E2
 Transport category (ADR) : 2
 Hazard identification number (Kemler No.) : 83
 Orange plates :



Tunnel restriction code (ADR) : D/E
 EAC code : •3W
 APP code : A(fl)

Transport by sea

Special provisions (IMDG) : 274
 Limited quantities (IMDG) : 1 L
 Excepted quantities (IMDG) : E2
 EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-C
 Stowage and handling (IMDG) : SW1, SW2

Air transport

PCA Excepted quantities (IATA) : E2
 PCA Limited quantities (IATA) : Y840
 PCA limited quantity max net quantity (IATA) : 0.5L
 PCA packing instructions (IATA) : 851

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

PCA max net quantity (IATA) : 1L
CAO max net quantity (IATA) : 30L

Inland waterway transport

Classification code (ADN) : CF1
Special provisions (ADN) : 274
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Additional requirements/Remarks (ADN) :

Rail transport

Classification code (RID) : CF1
Special provisions (RID) : 274
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Transport category (RID) : 2
Hazard identification number (RID) : 83

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
Reference code	Applicable on
3(a)	Instru Suc ; propan-2-ol ; ethanol
3(b)	Instru Suc ; propan-2-ol ; 2-(2-butoxyethoxy)ethanol ; ethanol
3(c)	Instru Suc
40.	Instru Suc ; propan-2-ol ; ethanol
55.	2-(2-butoxyethoxy)ethanol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Other information, restriction and prohibition regulations : Take note of Directive 94/33/EC on the protection of young people at work.

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000
E1 Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200

15.1.2. National regulations

United Kingdom

National regulations : This safety data sheet is for informational purposes only and does not comply with national legal requirements without reference to a national distributor. The national distributor is responsible for a legally compliant safety data sheet.

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
2.2	EUH-statements	Removed	
3	Composition/information on ingredients	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

Data sources : ECHA (European Chemicals Agency). MSDSs of the suppliers. Information provided by the manufacturer.

Instru Suc

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Department issuing data : KFT Chemieservice GmbH
specification sheet: Im Leuschnerpark 3
D-64347 Griesheim

Phone: +49 6155-8981-400
Fax: +49 6155 8981-500
SDS Service: +49 6155 8981-522

Contact person : Barbara Stark
Other information : Version/s 1.00-4.00 is/are not available in this language.

Full text of H- and EUH-statements:

Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 2	H411	Calculation method

KFT SDS EU 01

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.